NEW

SMART

Our modern compact parasol with a minimalist design





Assortment

	Nominal size without flounce	Number of ribs	Order no. Frame matt white	Order no. Frame anthracite
	cm			
\bigcirc	Ø 200	6 parts	208 00 200 161	208 00 200 301
	Ø 220	8 parts	208 00 220 161	208 00 220 301
	Ø 250	8 parts	208 00 250 161	208 00 250 301
	Ø 300	8 parts	208 00 300 161	208 00 300 301
	200×200	8 parts	208 00 201 161	208 00 201 301
	240×240	8 parts	208 00 241 161	208 00 241 301
	210×150	6 parts	208 00 212 161	208 00 212 301
	250×200	6 parts	208 00 252 161	208 00 252 301


Nominal size	e Lateral distance	Pole Ø	Area covered	Height closed	Clear headroom	Total height	Clearance height, parasol part inclined	Total height, parasol inclined	Foundation	Minimum weight for base	max. wind speed open perm.
cm	cm	cm	m²	cm	cm	cm	cm	cm	cm	kg	km/h (wind force)
A	AS	М	В	E	F	G	K	L	С		
Ø 200	175	3.6	2.6	85135	160210	185235	105155	215265	40x40	30	75 (9)
Ø 220	205	3.6	3.4	80130	160210	190240	100150	220270	40x40	30	65 (8)
Ø 250	230	3.6	4.4	65115	160210	190240	90140	225275	50x50	40	50 (7)
Ø 300	275	3.6	6.4	4595	160210	195245	75125	235285	60x60	40	35 (5)
200 x 200	-	3.6	4.0	4595	160210	185235	100150	210260	40x40	40	50 (7)
240 x 240	-	3.6	5.8	2575	160210	195245	90140	220270	50x50	40	40 (6)
210 x 150	-	3.6	3.2	60110	160210	190240	115165	200250	40x40	30	55 (7)
250 x 200	-	3.6	5.0	3585	160210	195245	105155	210260	50x50	40	40 (6)

The listed measures represent extrapolated average values that may be slightly different on the product ($\pm\,2\,\%\,\pm\,5\,$ cm).


Height dimensions are based on ground socket BT. These vary slightly depending on the type of base. Except for steel base minus 5 cm.

The max. wind speed limits as per our separate sheet apply only if the parasol canopy is in a horizontal position and if there is a fix ground anchorage. A base with the specified minimum weight is not sufficient.


 $In the presence of several parasols, the minimum distance between one parasol and another and between parasols and walls shall be 20 \, cm. \\$





Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), Guarantee water drainage



6 parts

















8 parts











11







	Accessories	Absolutely necessary	Order no.
	Protective cover made of coated, tear-resistant polyester fabric		
1	Protective cover with zip and rod		350 01 609 980
	10 pieces, protective cover with zip and rod		350 01 609 974
	Electrical accessories		
-	OSYRION Spot LED battery-powered light, set of 2, with remote control, including charger		350 01 563 000
3	OSYRION Spot LED battery-powered light, set of 4, with remote control, including charger		350 01 563 100
	Fixations	Absolutely necessary	Order no.
	Ground sockets		
4	Ground socket BT, hot-dip galvanised steel	Connection tube BT	350 01 206 100
	Wall consoles		
	Wall bracket Z, 180 mm, hot-dip galvanised steel	Support tube Z	350 01 205 000
	Bases		
3	Concrete base Z, 30 kg, Ø 47 × 10 cm, light concrete NEW	Support tube Z	350 01 111 016
5	Concrete base Z, 40 kg, Ø 60 × 8.5 cm, light concrete NEW	Support tube Z	350 01 111 116
	1 pallet (20 pieces) concrete base Z, 40 kg, Ø 60×8.5 cm, light concrete NEW	Support tube Z	350 01 112 116
	¹Concrete base Z, 40 kg, Ø 60×8.5 cm	Support tube Z	350 01 109 529
	¹ 1 pallet (20 pieces) concrete base Z, 40 kg, Ø 60×8.5 cm	Support tube Z	350 01 109 533
,	1/2 Natural granite base Z, 30 kg, 50×33×7 cm, natural stone NEW	Support tube Z	350 01 109 480
	Steel base Z 40 kg, 58.5×58.5×2 cm, hot-dip galvanised steel NEW	Support tube Z	350 01 100 810
8	¹ Steel base Z 40 kg, 58.5×58.5×2 cm, hot-dip galvanised steel	Support tube Z	350 01 100 210
_	Bases with castors		050.04.400.405
9	3 Natural granite base Z, 40 kg, 45 \times 45 \times 8 cm, natural stone, with castors and retractable handle	Support tube Z	350 01 109 465
9	3 Natural granite base Z, 55 kg, 55 \times 55 \times 9 cm, natural stone, with castors and retractable handle	Support tube Z	350 01 109 445
10	³ Base with castors Z, 55 kg, 65 × 65 × 11 cm, light concrete (without decorative plate)	Support tube Z + deco plate	rative350 01 113 200
	$^{\rm 3}$ 1 pallet (5 pieces) base with castors Z, 55 kg, 65 \times 65 \times 11 cm, light concrete (without decorative plate)	Support tube Z + deco plate	rative350 01 113 280
_	Decorative plate in grey white RAL 9002 for base with castors Z, 55 kg, aluminium composite		350 01 113 310
	Decorative plate in anthracite RAL 7016 for base with castors Z, 55 kg, aluminium composite		350 01 113 320
	Support tubes/Connection tubes		
11	Support tube Z, internal, Ø 30 / 25 mm, hot-dip galvanised steel NEW		350 01 201 710
12	Connection tube BT, internal, Ø 30/25 mm, hot-dip galvanised steel, incl. cover matt white NEW		350 01 201 916
	Connection tube BT, internal, Ø 30/25 mm, hot-dip galvanised steel, incl. cover anthracite NEW		350 01 201 930
	Various fixation types		
13	Lawn spike Z, 85×150×350 mm, hot-dip galvanised steel	Support tube Z	350 01 205 400
14	Wall consoles U for the table top, Ø 31–40 mm, high-grade steel 1.4301/304, for horizontal flat railing, square profile up to 120 mm		350 01 252 005

¹ while stocks last

furniture design house.com

Extreme outdoor furniture... handcrafted in Europe... Yet, surprisingly affordable!

Furniture Designhouse Ho Ho Kus, NJ 07423 201.689.9422 sales@FurnitureDesignhouse.com

 $[\]ensuremath{^{\text{3}}}$ only suitable for smooth, joint free surface coverings

SMART







Frame 6 or 8 parts

Pole Ø 36 mm Premium design

Function: internal support tube, quick opening and closing with clever sliding mechanism

Infinitely variable height adjustment up to 50 cm, tilts 32° in both directions

Ideal for balconies

Canopy self-tensing through flexible rib ends Frame roof: round, square, rectangular

Fabric corners reinforced with leather (Fabric Quality 5, 4)

Frame colour Matt white or anthracite powder-coated aluminium

Canopy Fabric Quality 5: polyacrylic, 300 g/m², UV protection > 98 %

Flounce Only available without

Protective cover Can be ordered as an optional extra


Electrical accessories Osyrion Spot LED with integrated battery pack











Valid from 1.1.2024 glatz.com